

FRESADORA CONVENCIONAL, M250C (M250D), M300 (M300A) e M330 (M330A)

SPECIFICATION		UNIT	M250C (M250D)	M300 (M300A)	M330 (M330A)
Table size		mm	254x1270/254x1370	305x1370/305x1500	330x137/330x1500
Longitudinal travel (X)		mm	820/920	870/1000	820/1000
Cross travel (Y)		mm	410	360	380
Vertical travel (Z)		mm	400	380	460
T-slot (No./width)		mm	3/16	3/16	3/16
Ram travel		mm	470	500	500
Distance from spindle to table		mm	0-400	0-350	0-450
Spindle taper		-	ISO40	ISO40	ISO40
Spindle quill travel		mm	127	127	127
Spindle speed		rpm	16steps, 50HZ: 65-4500/60HZ: 80-5440 (Optional: Variable 65-3750)		
Spindle quill automatic feed		mm/r	0.038/0.076/0.152	0.038/0.076/0.152	0.038/0.076/0.152
Main motor power		kw	3.7	3.7	3.7
Mill head swivel angle		°	±90°	±90°	±90°
Mill head tilting angle		°	±45° (Fix)	±45° (Fix)	±45° (Fix)
X/Y/Z-axis guide type		-	▲ ■ ■	▲ ■ ■	▲ ■ ■
Dimension of package	One	mm	1516x1550x2080	1566x1650x2080	1800x2020x2200
	Two	mm	1650x1790x2170	1720x1800x2175	1800x2200x2180
Gross weight (One)		kg	1490	1650	2200